




WOOD SHELL BLOCKS



Made in Peru



⚠ Never Exceed Working Load Limit

Sheave Size	Rope Dia. (in.)	Sheave Dimensions			Working Load Limit			Weight of Blocks		
		Outside Dia. (in.)	Rim Thickness (in.)	Center Pin Dia. (in.)	Single Sheave Capacity in Lbs.	Double Sheave Capacity in Lbs.	Triple Sheave Capacity in Lbs.	Single Sheave Wt. Per Block in Lbs.	Double Sheave Wt. Per Block in Lbs.	Triple Sheave Wt. Per Block in Lbs.
4	1/2	2 1/4	5/8	3/8	1,014	1,411	1,807	2.0	2.6	3.3
5	5/8	3	3/4	3/8	1,212	1,807	2,424	3.5	4.8	7.3
6	3/4	3 1/2	1	1/2	1,807	2,513	3,218	4.4	7.5	8.8
7	7/8	4 1/2	1	1/2	2,204	3,019	4,011	6.2	9.0	15.8
8	1	4 3/4	1 1/8	5/8	2,821	3,813	4,849	7.9	13.9	18.6
10	1 1/4	6 1/4	1 1/4	5/8	4,011	6,017	8,023	13.2	27.5	35.6
12	1 1/2	8	1 3/8	3/4	5,025	8,023	10,028	22.0	34.8	63.8

FITTED WITH:

- SHACKLE
- FIXED HOOK
- SWIVEL SHACKLE

Beautifully constructed of Lagarto tropical hardwood.

